



## ROAD SAE 5W/40



### DESCRIPTION:

ROAD is a synthetic super multigrade oil developed to meet the lubrication needs of the last generation motorcycles with 4-stroke engines.

ROAD ensures optimum engine lubrication even at high running temperatures. ROAD keeps the engine and the sparkplugs clean to offer highest efficiency and performance.

ROAD protects the engine from wear, prolonging the life of the moving parts; in particular the special extreme-pressure additives guarantee protection of the gears in the engine.

ROAD, thanks to the special formulation, allows easy starting even in very cold weather as well as reduced fuel consumption.

ROAD ensures perfect oil-bath clutch operation under any condition and duty, avoiding problems of clutch slip.

### APPLICATIONS:

ROAD is a oil developed to meet the lubrication needs of the last generation motorcycles with 4-stroke engines.

### SPECIFICATIONS – HOMOLOGATIONS:

API SM; JASO MA-2

### SECTORS OF APPLICATION:



### THIS PRODUCT IS RECOMMENDED BY:



## PACKAGING

---

Bottle : 1 lt

Can : 5kg

Tin : 18kg

Drum : 50Kg

Barrel : 180Kg

---

## TYPE

---

Synthetic Base : ✓

---

## TECHNICAL SPECIFICATIONS

---

SAE : 5W 40

API : SL

Viscosity DIN 51562 40°C : 65

Viscosity DIN 51562 100°C : 10,5

Viscosity index ISO 2909 : 150

Density 15°C DIN 51757 Kg/dm<sup>3</sup> : 0,85

TBN mg KOH/g: 8,3

Minimum temperature for pumpability °C : -25

---

## APPLICATIONS

---

Engine : ✓

---